



序号 No.	主要技术参数 Main Technical Specification	型号 Type	
		TF-7.2/200-10	
电气参数 ELECTRIC RATINGS			
1	额定电压 Rated Voltage	kV	7.2
2	额定电流 Rated Current	A	200
3	额定频率 Rated Frequency	Hz	50/60
4	额定短时(1分钟)工频耐受电压 Rated Short-time(1min) Power-Frequency Withstand Voltage	kV	25
5	额定触头压力下限时的回路电阻 Circuit Resistance At Lowest Rated Contact Force	$\mu\Omega$	≤ 100
6	雷电冲击耐受电压 Lightning Impulse Withstand Voltage	kV	60*
7	额定短时耐受电流 4秒 Rated Short-time Withstand Current, 4s	kA	10
8	额定峰值耐受电流 Rated Peak Withstand Current	kA	25
9	额定短路关合电流 Rated Short-circuit Making Current	kA	25
10	额定有功负载开断电流 Rated Active Load Breaking Current	A	10
11	额定闭环开断电流 Rated Closed-loop Breaking Current	A	200
寿命 LIFE			
1	机械寿命 Mechanical Life	Times	50000
2	储存时间 Storage Life	years	≥ 20
3	触头允许磨损厚度 Contacts Erosion Limit	mm	3
机械数据 MECHANICAL DATA			
1	触头自闭力 Contact Force From Atmosphere	N	12 \pm 6
2	触头反力 Counterforce of Contacts at Full Stroke	N	/
配套的真空开关设备应满足的机械参数 MECHANICAL DATA OF VACUUM SWITCH EQUIPPED WITH THE INTERRUPTERS			
1	触头开距 Contact Stroke	mm	3.5 \pm 0.5
2	超行程 Overtrave	mm	2
3	平均分闸速度 Average Opening Speed	m/ s	1.1 \pm 0.2
4	平均合闸速度 Average closing speed	m/ s	0.6 \pm 0.2
5	触头合闸弹跳时间 Contact Bouncing Duration at Cosing Operation	ms	≤ 2
6	额定触头压力 Rated Added External Contactfinal Force	N	300

TF-7. 2/200-10

负荷开关用真空灭弧室

Vacuum Interrupter For Load-breaking Switch

AA: 生产年份;
 BB: 该年的第几周;
 000: 生产编号。

